

PHILIPS

CarePoint



CarePoint Paging Staff Communication

CarePoint paging is an option to dispatch alarms from the central monitoring station to staff members caring for residents around the building.

If your community elects to use pagers for staff to receive system alarms, CarePoint will be configured with the hardware needed to quickly dispatch pages to staff. Your community can customize the number or devices receiving alarms, and create groups allowing messages to be directed to the appropriate team members across your campus.

Features

Provides coverage on a variety of campus sizes

Covered by back up paging, which allows staff to still receive alarms in the event the computer station is unavailable

Can be configured to alarm with one of 14 different audible notifications or vibrate to provide an unobtrusive alarm notification

Convenient for staff to carry on a belt clip or in a pocket

Alerts can easily be seen on large LCD display which displays 4 lines of text including alarm information and any special notes which may be critical when providing care to residents

Simple to use and maintain with user friendly interface, one button delete and long battery life

Available in multiple colors allowing assignment of pagers to specific regions of the facility or to staff. Provides easy identification.

Specifications

Pagers

Color	Black, Red, Blue, or Green
Frequency	Frequency 408-473MHz
Dimensions	80(L) x 53(W) x 20(H) mm
Viewing Area	46 x 17.36 mm
Display	One Page 4-Lines Total 84 Alphanumeric
Screen	Large Blue Back Light
Performance	Extra Long Battery Life
Alerts	4 Beep Alerts, 10 Melody Alerts
Alert Tone	Loudness 85db @ 30 cm (12 inches)
Alarms	5 Daily Alarm Sets
Modes	Vibration and Sleep Modes
Indicators	Unread Message, Message Full Indicators, Message Time Stamp
Detection	Duplicate Message
Auto Features	Sleep/Scroll
Memory	16 Memory Slots, 10 Sets
Locks	8 Message Locks

Paging Transmitter

Color	Black
Frequency	Frequency 408-473MHz
Dimensions	9" H x 8.5" W x 2.25" D
Frequency Range	UHF2 (440 – 470MHz) UHF1 (400-430MHz)
Power Output	2 Watts, 5 Watts, 25 Watts
Transmitter FCC ID	RXUSD-125EU2 (Maxson)
Transmitter Canada ID	153B-SD125EU2 (Maxson)
Power Supply Input	12vDC 3.75A (of Higher Amp) AC/DC Adaptor
Operating Temperature	22° F to 140° F
Weight	8.5 lbs.

Ordering Information

Description	Part Number
Black Pager, Alphanumeric, 4 lines	1900497
Red Pager, Alphanumeric, 4 lines	1901000
Blue Pager, Alphanumeric, 4 lines	1901001
Green Pager, Alphanumeric, 4 lines	1901002
Paging Transmitter, 2 Watt, 467.8 MHz	1900500
Paging Transmitter, 2 Watt, 469.6 MHz	1900501
Paging Transmitter – 5 Watt 469.6 MHz	1900498

